

ECOLOGICAL BRICK FOR SLOPE LANDS

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The invention relates to an ecological brick for slope lands and particularly to a brick that has water retaining and permeable properties and has space for growing plants and interconnecting means to serve as construction material for slope lands.

2. Description of the Prior Art

10 Some land development projects such as building roads or construction engineering usually involve slope land development. Plants do not cover the excavated slope land and crumbling often occurs. Hence land protection engineering is very important after the slope land is formed. The most commonly approach to mend the slope land at present is
15 to build a manmade sloping bank. It is generally a small slope and stepwise construction with a trapezoid gradient to avoid the slope land from sliding caused by the steep land surface after construction. Moreover, the slope land usually is covered by cement grouting or a Ferro-concrete protection wall. These protection measures have disadvantages, notably

the land surface cannot grow plants. Hence the slope land cannot be restored to its original landscape. In addition, the cement slope land has to reserve water vents to allow water in the soil to seep out and discharge. During heavy rain, water accumulates in the soil rapidly and often cannot
5 be drained effectively. It often happens that the slope land cannot withstand the huge inner pressure and results in collapse or landslide. There is other type of slope land protection approach that adopts serpentine cages or stacking rocks. While this approach enables the slope land to partly restore to its original condition, and its surface has more
10 irregular drain gutters to infiltrate water from the soil at the earlier stage and reduce the pressure that might otherwise cause crumbling, it also has the disadvantage existed in the cement wall, i.e. difficult to grow plants. Although the rocks or serpentine cages have some cracks to allow weeds to grow, it is difficult to cultivate desired plants on desired locations. The
15 contemporary methods of systematic cultivating plants on the slope land mostly are to cover the slope land with meshes and grow the plants thereon. However, such type of planting merely is limited to crawling plants such as vines.

Thus the prior approach of cementing the slope land is against the
20 water drain principle of the natured slope land and is prone to cause crumbling, and the surface cannot grow plants. While the rock-type slope land offers some improvements over the cemented slope land, growing of

the plant is difficult to control.

SUMMARY OF THE INVENTION

In view of the aforesaid disadvantages, the object of the invention is
5 to provide a novel brick for slope lands that is made from virgin materials
or wasted materials. The brick of the invention, whether it is made from
the virgin materials or wasted materials, has a common feature of being
formed in a porous structure. Thereby excessive water may be drained
quickly on the slope land. Because the slope land built by the material of
10 the invention can drain water effectively, crumbling can be prevented. The
brick for slope lands of the invention further provides a space for growing
plants. Thus forestry or planting condition on the slope land may be
designed and cultivated to match the surrounding to improve the
environment and protect the slope land. The porous structure of the brick
15 for slope lands also can retain water to enable the soil under the brick to
infiltrate water to nourish the plants growing in the planting space of the
brick, therefore the plants may grow without additional human watering
and management is easier. The porous brick that has good water
permeability and retention properties also offers better sound absorption
20 capability. Thus it can reduce noise level of the heavy traffic on the
road bordering the slope lands.

The brick for slope lands according to the invention may be made in the form of a general rock or brick. It may be stacked and bonded by cement to form a slope land. In one aspect of the invention, the brick is formed in a structure for interconnection, such as having through holes or
5 cavities that are coupled by reinforced bars or insert pins to engage with one another. In addition, the peripheral sides of the brick may also have a wedging structure to allow the brick to couple and stack and assemble without using external connection elements.

In short, the invention aims at providing an improved brick for slope
10 lands to effectively overcome the shortcomings occurred to the conventional slope land construction.

The foregoing, as well as additional objects, features and advantages of the invention will be more readily apparent from the following detailed description, which proceeds with reference to the accompanying drawings.
15

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of the invention.

FIG. 2 is a longitudinal cross section of FIG. 1.

FIGS. 3, 4 and 5 are schematic views of the embodiments of the
20 invention in various stacking and coupling conditions.

FIG. 6 is a front view of an embodiment of the invention adopted for

use on a sloped land.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Refer to FIG. 1 for an embodiment of the invention. The brick 1 of
5 the invention is made from virgin materials or waste materials and formed
in a porous structure that has excellent water permeable and retaining
properties. The porous bricks equipping with such properties are known in
the art, details are omitted. The brick 1 has a space 11 for growing plants,
preferably on an upper portion of one surface. The space has an opening
10 111 on the surface of one end of the brick 1 and a cavity 112 located
deeply in the interior of the brick 1 (as shown in FIG. 2). There are two
apertures 12 located at two sides of the space 11 that may be through holes
running through the brick 1 or cavities of a selected depth. If the aperture
is a through hole 13, an elongated reinforced bar 21 may run through the
15 hole 13 to couple and assemble the bricks 1 (as shown in FIG. 3). If the
aperture is a cavity 14, an insert pin 22 may be inserted to couple the brick
1 (as shown in FIG. 4). The cavity may be formed in longitudinal manner
or transverse manner. Moreover, asides from coupling by external
elements such as elongated reinforced bar 21 and pin 22, the brick may
20 also be formed with a self-latching structure. FIG. 5 illustrates a brick 3,
which has mail dovetail coupling troughs 31 and female dovetail coupling

troughs 32 that may be wedged and coupled with one another to form a slope land.

The cavity 112 in the space 11 can grow a desired plant 41, which is not limited to vines. The cavity 112 may contain soil 42 to grow the plant
5 41. The soil 42 is retained by a stopping wall 113 at the front end of the cavity 112 (as shown in FIG. 2). After the brick 1 is stacked layer by layer (as shown in FIG. 6), the cavity 112 is covered by the bottom of the brick 1 of an upper layer. Thus rainwater does not directly flow down into the cavity 112 from above and does flush away the soil 42. Therefore the
10 invention can provide an excellent growing environment for plants.